

Release Notes

SwyxDECT 800

Product Version: Firmware Pack v.11.8.10 (v1)

Status: "General Availability"

Enreach GmbH
Emil-Figge-Straße 86
44227 Dortmund
Germany

No of pages: 8
Version: 1.0
Last Changes: 30.1.2023

Contents

1. C	ontent of Product Release	3
1.1.	SwyxDECT 800	3
2. D	ocument History	3
3. P	roduct Version History	3
3.1.	Understanding the SwyxDECT 800 Firmware Version Format	3
4. C	hanges	4
4.1.	New with Firmware Pack v.11.8.10 (v1)	4
4.2.	New with Firmware Pack v.11.4.4 (v2)	4
4.3.	New with Firmware Pack v.11.4.4 (v1)	5
5. S	wyx-DECT Integration vs. Standard Installation	5
5.1.	Go or No-Go:Is Your System Ready for Swyx DECT-Integration?	5
5.2.	Provisioning of the Firmware Package	6
6. A	dditional Information	6
6.1.	Technical Improvements	6
6.2.	Temporary Restrictions	6
6.3.	Permanent Restrictions	6
7. In	nstallation	6
7.1.	Update Processes	6
7.2.	Important Configuration	7
8. S	upported Devices	8
9. S	upported SwyxWare Versions	8
10.S	upport	8
		8

1. Content of Product Release

1.1. SwyxDECT 800

Component	Filename	Version/Build
SwyxDECT Base station IP800	IPBS1 11.8.10.zip	v.11.8.10
	IPBS2 11.8.10.zip	
	IPBS3 11.8.10.zip	
SwyxPhone D843	d43_v2.15.3.zip	v.2.15.3
SwyxPhone D863	d63_v2.15.3.zip	v.2.15.3
SwyxPhone D881	d81_v4.16.2.zip	v.4.16.2
SwyxPhone D883	d83_v1.4.5.zip	v.1.4.5
IP-DECT Gateway IPBL	IPBL1 11.8.10.zip	v.11.8.10

2. Document History

Version	Date	Remarks	Editor
1.0	27.01.2023	Initial creation for Product release version v.11.8.10 (v1)	Product Management

3. Product Version History

Version	Date	Remarks
11.8.10 (v1)	31.01.2023	Maintenance Version, Usable with Swyx 13.x
11.4.4 (v2)	02.12.2022	Support of D883, Maintenance Version, Usable with Swyx 13.x
11.4.4	31.08.2021	Support Swyx DECT Integration, Usable with Swyx 13
11.3.4	08.02.2021	Bugfix Version
11.1.5	20.09.2020	Bugfix Version
10.3.5	25.04.2019	Created for minor release

3.1. Understanding the SwyxDECT 800 Firmware Version Format

Firmware for the SwyxDECT 800 DECT system will be released always in form of a firmware packages which contain the released firmware version for the base station and the different handset types.

The versioning of the firmware package is orientated on the firmware version of the base station. (here v.11.8.10)

The version numbering in brackets (here v1) indicates following versions with additional handset firmware releases. As a rule of thumb this handset firmware versions are bug-fix releases and should be installed, if you have any issues with your system. From there you should read this release notes carefully to understand if the current release fixes an open issue and/or can add additional value to your system

This handset firmware versions will be tested and released by the Enreach QA against the initial base station firmware version of the related package.

4. Changes

4.1. New with Firmware Pack v.11.8.10 (v1)

The following issues are fixed within this package

- DECT-Integration: When a handset is roaming, missed calls are deleted from the Swyx Call Journal. (SwyxPhone D881) Fixed
- DECT-Integration: When a handset is roaming, the keypad lock is enabled/disabled (SwyxPhone 881) - Fixed
- DECT Integration: Firmware update Over-the-Air does not work (SwyxPhone D883 only) Fixed
- DECT-Integration: If DHCP is disabled on the Master, it is also disabled on every radio in the system resulting in the default 192.168.0.1 IP-address Fixed

Known issue:

- Consultancy call from phonebook (1st call on hold) fails (SwyxPhone D883 only).
- DECT-integration: Memory leak causes the re-start of a handset (SwyxPhone D863 only)

4.2. New with Firmware Pack v.11.4.4 (v2)

The following issues are fixed within this package

- Introduction of the new firmware package deployment. From now on new firmware for the SwyxDECT 800 system will be released in packages always.
- DECT-Integration: When a handset is roaming, missed calls are deleted from the Swyx Call Journal. (SwyxPhone D843, D863)
- DECT-Integration: When a handset is roaming, the keypad lock is enabled/disabled (SwyxPhone D843, D863)
- DECT-Integration: If the firmware update over-the-air is interrupted by a call, the download speed will not be re-adjusted to the initial rate again after the call.
- If the hook-off button is pressed during a call in CTI+ mode, the call is put on hold.

In addition, the new package also provides some new functions

- DECT-integration: Softkeys are now supported also in the D843 handset.(D843)
- DECT-Integration: Support of the new SwyxPhone D883. Prerequisite is the use of Swyx 13.25. At a classic installation the D883 is also supported with a Swyx 13.20 or smaller. (D883)

Known issue:

- DECT-Integration: When a handset is roaming, missed calls are deleted from the Swyx Call Journal. (SwyxPhone D881 only)
- DECT-Integration: When a handset is roaming, the keypad lock is enabled/disabled (SwyxPhone D881 only)
- DECT Integration: Firmware update Over-the-Air does not work (SwyxPhone D883 only)
- Consultancy call from phonebook (1st call on hold) fails (SwyxPhone D883 only).

4.3. New with Firmware Pack v.11.4.4 (v1)

In combination with SwyxWare 13 the firmware v11.4.4 is required for the new function "DECT-Integration" for SwyxDECT 800.

Important remark: For the initial installation of a new or before the update of an already existing SwyxDECT 800 system, please check carefully if your environment meets the requirements to run the new Swyx DECT Integration functionality.

Hint: With the new firmware the CTI+ functionality in certain transfer scenarios is improved. The Swyx DECT integration sets this configuration item manually, in conventional scenarios the setting must set manually on the DECT master:

- Please check the option "SIP" for the item "Allow Multiple Codecs in Answer SDP". The option can be found under Configuration/VoIP/SIP on the DECT Master BS Web UI.

5. Swyx-DECT Integration vs. Standard Installation

With Swyx 13 SwyxDECT 800 can be operated in 2 different modes.

- Swyx DECT Integration: For the initial operation of the new DECT Integration functionality the DECT Master must be updated to the latest firmware version (at least v.11.4.4.). The update of the slave antennas and the handsets is then done automatically as part of the DECT Integration service.
- Standard installation without Swyx DECT Integration support: If your SwyxDECT 800 system does not meet the requirements for using the Swyx DECT Integration service (see below), you can continue to operate the system as usual. The update of the base stations will then be done as before, as well as the update of the handsets via the optional programming cradles or Ascom Unite.

5.1. Go or No-Go:ls Your System Ready for Swyx DECT-Integration?

Ascom as the OEM vendor of SwyxDECT 800 offers various Add-Ons, which allows the usage of SwyxDECT 800 in different scenarios. Not all this Add-Ons are supported by the Swyx DECT Integration until now. Please carefully check your system before you decide to go for the Swyx DECT Integration or the standard installation path.

The following scenarios and configurations are not supported until now by the new Swyx DECT Integration

- Mirroring
- Usage of Ascom Unite
- Ascom IP-DECT GW for TDM base stations
- Different Sync Master (Can be configured manually after initial set-up)

- Different IP Subnets (Base stations in other subnets than the Master can be configured manually)
- IP-BS1: The legacy base station is not supported.
- SwyxPhone D21x/31x: This legacy handsets are not supported.

5.2. Provisioning of the Firmware Package

For installations with Advanced Swyx DECT-Integration, the firmware package is automatically made available in the Swyx Control Center in a timely manner. For installations whose components are updated via a local software distribution, as well as for standard installations, suitable firmware packages will be made available for download in the Enreach Partner Net.

6. Additional Information

6.1. Technical Improvements

Detailed information on technical improvements can be found in ASCOM release notes, attached to help center article and in the Swyx Online Help.

6.2. Temporary Restrictions

Please note that the operation of multiple independent SwyxDECT 800 systems within the same network segment may lead to complications. If this constellation exists, please update all base station in the network segment to the present version. After that the systems can be logically separated within the Swyx Control Center.

6.3. Permanent Restrictions

With FW v.11.4.4 the legacy Swyx Standby scenario (Master/Slave-Standby) is no longer supported.

7. Installation

With the release of v.11.1.5 and v.2.6.6 the upgrade process of the base stations and devices may require additional steps to prevent unwanted behaviour of the hardware after the update process. Please follow the instructions of this chapter to upgrade SwyxDECT 800.

7.1. Update Processes

Information for updates to V11.4.4

SwyxDECT 800 must run on version 9.X.X or newer before updating to v.11.4.4.

Information for updates to V2.12.9

Nothing

7.2. Important Configuration

Deactivate ICE parameter

ICE parameter is enabled by default after the update to v.V11.3.4 and causes Voice problems.

Solution: <u>ICE parameter must be deactivated</u> for SwyxDECT800 to work correctly. The parameter can be found in "DECT -> System page".

Use of SMS feature

SMS encryption is enabled by default after the update. If SMS encryption is not wanted, it needs to be disabled both in Unite (see Unite documentation) and in the IPBS (see Installations and Operations manual).

8. Supported Devices

Туре	Product	Preferred Version
	SwyxPhone D31x Handset	v.4.3.17 (w/o DECT Int.)
	SwyxPhone D21x Handset	v.4.3.17 (w/o DECT Int.)
	SwyxPhone D843 Handset	v.2.15.3
	SwyxPhone D863 Handset	v.2.15.3
Devices	SwyxPhone D881 Handset	v.4.16.2
	SwyxPhone D883 Handset	v.1.4.5
	SwyxDECT 800 (IP-BS2/3)	v.11.8.10
	SwyxDECT 800 (IP-BS1)	v.11.8.10 (w/o DECT Int.)
	Ascom IBPL1	v.11.8.10 (w/o DECT Int.)

We recommend customers use the "Preferred Version" for the given products. The preferred software versions offer tested and confirmed level of functionality. However, the devices might also operate with older or newer software version with the caveat that recently added interoperability or advanced features may not be possible when using these versions. In cases, if a defect is found when using other versions, it may be necessary to update to the supported version.

9. Supported SwyxWare Versions

Product	Supported Version
Swyx	Swyx 13
SwyxOn	

We recommend customers use the "Released Version" for the given products. The supported software versions offer tested and confirmed level of functionality. However, the devices might also operate with older or newer software version with the caveat that recently added interoperability or advanced features may not be possible when using these versions. In cases, if a defect is found when using other versions, it may be necessary to update to the supported version.

10. Support

The Support for the SwyxDECT 800 is handled through the regular Swyx Support process.

11. Documentation

The current documentation can be found on Swyx Help Center.

https://help.swyx.com/docs/manuals/eng-

lish/SwyxDECT800.pdfhttps://service.swyx.net/hc/en-gb/articles/360000631445-Technical-Documentation-Swyx-DECT-800-SwyxPhone-D210-D310-D311BT-D843-and-D863-